



Rzędna terenu	31,0		61,0		19,5		36,5		46,50		66,00		10,00		130,50		127,00		161,50	
	dz90PE		dz160PE		dz160PE		dz160PE		dz160PE		dz160PE		dz160PE		dz160PE		dz160PE		dz160PE	
Rzędna osi rurociągu [m]	1,90	1,75	1,76	1,75	1,90	2,00	1,90	1,88	1,90	1,90	1,90	1,90	1,90	1,90	1,90	1,90	1,90	1,90	1,90	
Zagłębienie osi rurociągu	120,25	120,10	120,09	120,10	119,85	119,75	119,35	119,32	119,35	119,35	119,35	119,35	119,35	119,35	119,35	119,35	119,35	119,35	119,35	
Odstępnice, materiał	3,5		6,5		1,1%		0,5%		0,5%		0,5%		0,5%		0,5%		0,5%		0,5%	
Długość trasy [m]	121,85		121,85		121,75		121,25		121,25		121,25		121,25		121,25		121,25		121,25	
Średnice, materiał	5,0		9,0		17,0		9,5		18,0		7,0		5,0		22,0		9,5		5,0	
	dz63PE		dz160PE		dz160PE		dz160PE		dz160PE		dz160PE		dz160PE		dz160PE		dz160PE		dz160PE	
Długość trasy [m]	98,50		83,50		47,00		56,50		74,50		90,50		98,50		22,00		31,50		56,50	
Średnice, materiał	20,0		20,0		20,0		20,0		20,0		20,0		20,0		20,0		20,0		20,0	
	dz83PE		dz83PE		dz83PE		dz83PE		dz83PE		dz83PE		dz83PE		dz83PE		dz83PE		dz83PE	
Długość trasy [m]	0,00		0,00		0,00		0,00		0,00		0,00		0,00		0,00		0,00		0,00	